

# ENVIRONMENTAL PRODUCT DECLARATION

IN ACCORDANCE WITH EN 15804+A2 & ISO 14025 / ISO 21930

## SWEDOOR ADVANCE-LINE EXTERIOR

EXTERIOR DOORSETS 77 mm, UNGLAZED, ECO, RC3

### JELD-WEN



**EPD HUB, HUB-1526**

Publishing on 11.07.2024, last updated on 11.07.2024, valid until 11.07.2029

## GENERAL INFORMATION

### MANUFACTURER

Manufacturer	JELD-WEN
Address	Retford Road, Woodhouse Mill, Sheffield, South Yorkshire, S13 9WH
Contact details	eu_sustainability@jeldwen.com
Website	www.jeld-wen.biz

### EPD STANDARDS, SCOPE AND VERIFICATION

Program operator	EPD Hub, hub@epdhub.com
Reference standard	EN 15804+A2:2019 and ISO 14025
PCR	EPD Hub Core PCR version 1.1, 5 Dec 2023
Sector	Construction product
Category of EPD	Third party verified EPD
Parent EPD number	
Scope of the EPD	Cradle to gate with options, A4-A5, and modules C1-C4, D
EPD author	Piia Peever
EPD verification	Independent verification of this EPD and data, according to ISO 14025: <input type="checkbox"/> Internal verification <input checked="" type="checkbox"/> External verification
EPD verifier	Imane Uald lamkaddam, as an authorized verifier acting for EPD Hub Limited

The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of construction products may not

be comparable if they do not comply with EN 15804 and if they are not compared in a building context.

### PRODUCT

Product name	SWEDOOR ADVANCE-LINE Exterior doorsets 77 mm, unglazed, ECO, RC3
Additional labels	ADVANCE-LINE Character ADVANCE-LINE Classic ADVANCE-LINE Function ADVANCE-LINE custom designs
Place of production	Aizkraukle, Latvia
Period for data	Calendar year 2021
Averaging in EPD	No averaging

### ENVIRONMENTAL DATA SUMMARY

Declared unit	one square meter (m <sup>2</sup> )
Declared unit mass	47.10 kg
GWP-fossil, A1-A3 (kgCO <sub>2</sub> e)	1,17E+02
GWP-total, A1-A3 (kgCO <sub>2</sub> e)	5,16E+01
Secondary material, inputs (%)	6.98
Secondary material, outputs (%)	75.3
Total energy use, A1-A3 (kWh)	644
Net fresh water use, A1-A3 (m <sup>3</sup> )	2.2

## PRODUCT AND MANUFACTURER

### ABOUT THE MANUFACTURER

Headquartered in Charlotte, N.C., USA, JELD-WEN is a leading global manufacturer of high-performance interior and exterior building products, offering one of the broadest selections of windows, interior and exterior doors, and wall systems. JELD-WEN delivers a differentiated customer experience, providing construction professionals with durable, energy-efficient products and labor-saving services that help them maximize productivity and create beautiful, secure spaces for all to enjoy. The JELD-WEN team is driven by innovation and committed to creating safe, sustainable environments for customers, associates, and local communities. The JELD-WEN family of brands includes JELD-WEN® worldwide; LaCantina™ and VPI™ in North America; Swedoor® and DANA® in Europe; and Corinthian®, Stegbar®, and Breezway® in Australia. Visit [JELD-WEN.com](http://JELD-WEN.com) for more information.

### PRODUCT DESCRIPTION

Advance-line exterior doorset RC3, including unglazed reinforced wooden door and frame, and standard hardware for installation. Doorleaf has 77 mm sandwich construction with wood fibre core, and it is installed together as a doorset with the average Swedoor-frameset for exterior doors. The scope of this EPD is the full doorset for module size of 9x21, depth of frame up to 210 mm. The reference size of 0,988 m x 2,080 m is used in the LCA to calculate the results for the declared unit (one square meter of the doorset). Product is suitable for use in both private and commercial buildings, with main area of use residential houses (1+2 dwellings). The doorset can be manufactured with classification option for 30 minute fire rating (EI<sub>1</sub> 30). The specific technical standards and additional product information for the designs and available classification options can be found on Swedoor website [www.jeld-wen.biz](http://www.jeld-wen.biz).

### PRODUCT RAW MATERIAL MAIN COMPOSITION

Raw material category	Amount, mass- %	Material origin
Metals	16	EU
Minerals	-	-
Fossil materials	8	EU
Bio-based materials	76	EU

### BIOGENIC CARBON CONTENT

Product's biogenic carbon content at the factory gate

Biogenic carbon content in product, kg C	19.99
Biogenic carbon content in packaging, kg C	1.63

### FUNCTIONAL UNIT AND SERVICE LIFE

Declared unit	one square meter (m <sup>2</sup> )
Mass per declared unit	47.10 kg

### SUBSTANCES, REACH - VERY HIGH CONCERN

The product does not contain any REACH SVHC substances in amounts greater than 0,1 % (1000 ppm).

# PRODUCT LIFE-CYCLE

## SYSTEM BOUNDARY

This EPD covers the life-cycle modules listed in the following table.

Product stage			Assembly stage		Use stage							End of life stage				Beyond the system boundaries		
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D		
x	x	x	x	x	MND							x	x	x	x	x		
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstr./demol.	Transport	Waste processing	Disposal	Reuse	Recovery	Recycling

Modules not declared = MND. Modules not relevant = MNR.

## MANUFACTURING AND PACKAGING (A1-A3)

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production as well as packaging materials and other ancillary materials. Also, fuels used by machines, and handling of waste formed in the production processes at the manufacturing facilities are included in this stage. The study also considers the material losses occurring during the manufacturing processes as well as losses during electricity transmission.

The product is made of solid wood, wood-based boards, metal parts, plastic parts and chemicals (glue and paint). The materials are transported to JELD-WENS production facility.

The production of the door begins with the gluing and pressing of the door materials. The door leaf is then milled to the correct dimensions and the lock and hinge holes are milled. Next, the door leaf moves to the surface

treatment, where the surface of the door leaf is primed and painted. After surface treatment, the lock, hinges and sealings are installed and the product will be packed.

Production waste and loss, including waste paint and cuttings of wood are sent to a waste management company to be incinerated; wastewater is treated in an average municipal treatment plant.

After packing, the product is ready to be shipped to end customer / construction site.

## TRANSPORT AND INSTALLATION (A4-A5)

Transportation impacts occurred from final products delivery to construction site (A4) cover fuel direct exhaust emissions, environmental impacts of fuel production, as well as related infrastructure emissions.

The transportation distance is calculated based on the product-specific sales data, taking into account the end customer locations; weighted average result is being used. The transportation method is assumed to be lorry and ferry. Vehicle capacity utilization volume factor is assumed to be 1 which means full load. In reality, it may vary but as role of transportation emissions in total results is small, the variety in load is assumed to be negligible. Empty returns are not taken into account as it is assumed that return trip is used by the transportation company to serve the needs of other clients. Transportation does not cause losses as product are packaged properly.

Installation includes the generated packaging waste. There is no loss on site during construction activities. Energy use during installation has not been taken into account, as installing the door only requires mounting and fastening. No additional materials are needed for installation.

## PRODUCT USE AND MAINTENANCE (B1-B7)

Air, soil, and water impacts during the use phase have not been studied.

**PRODUCT END OF LIFE (C1-C4, D)**

Consumption of energy and natural resources in demolition process is assumed to be negligible.


It is assumed that the waste is collected as mixed construction waste and transported to the waste treatment center. Transportation distance to treatment is assumed as 50 km and the transportation method is assumed to be lorry (C2).

Per the end of life scenario of timber windows and doorsets (EN17213 Annex B), the wood, metal, plastic, paint and glue are sorted. Module C3 accounts for energy and resource inputs for sorting and treating these waste streams for recycling and incineration with energy recovery.

Per the end of life scenario of timber windows and doorsets (EN17213 Annex B), 5% of wood, 5% of metal, 5% of plastic and 5% of paint and glue waste goes to landfill. Additionally, hazardous waste that is incinerated is included in Module C4 while the flow not included in Module D for benefits.

As specific national data is not used for timber / wooden products, then according to the end of life scenario of timber windows and doorsets (EN17213 Annex B), 100% of sorted timber materials goes to incineration. The wooden pallet, wooden board, cardboard packaging and plastic packaging used during transportation are also incinerated for energy recovery or recycled. The benefits and loads of incineration and recycling are included in Module D.

**MANUFACTURING PROCESS AND SYSTEM BOUNDARY**



# LIFE-CYCLE ASSESSMENT

## CUT-OFF CRITERIA

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. The study includes all major raw material and energy consumption. All inputs and outputs of the unit processes, for which data is available for, are included in the calculation. There is no neglected unit process more than 1% of total mass or energy flows. The module specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

## ALLOCATION, ESTIMATES AND ASSUMPTIONS

Allocation is required if some material, energy, and waste data cannot be measured separately for the product under investigation. All allocations are done as per the reference standards and the applied PCR. In this study, allocation has been done in the following ways:

Data type	Allocation
Raw materials	No allocation
Packaging materials	Allocated by mass or volume
Ancillary materials	Allocated by mass or volume
Manufacturing energy and waste	Allocated by mass or volume

## AVERAGES AND VARIABILITY

Type of average	No averaging
Averaging method	Not applicable
Variation in GWP-fossil for A1-A3	Not applicable

This EPD is product and factory specific and does not contain average calculations.

## LCA SOFTWARE AND BIBLIOGRAPHY

This EPD has been created using One Click LCA EPD Generator. The LCA and EPD have been prepared according to the reference standards and ISO 14040/14044. The EPD Generator uses Ecoinvent v3.8, Plastics Europe, Federal LCA Commons and One Click LCA databases as sources of environmental data.

# ENVIRONMENTAL IMPACT DATA

## CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP – total <sup>1)</sup>	kg CO <sub>2</sub> e	1,86E+01	8,76E+00	2,43E+01	5,16E+01	9,36E+00	6,04E+00	MND	0,00E+00	2,21E-01	5,99E+01	1,21E+01	-7,91E+01						
GWP – fossil	kg CO <sub>2</sub> e	8,66E+01	8,76E+00	2,13E+01	1,17E+02	9,35E+00	1,48E-01	MND	0,00E+00	2,21E-01	2,88E+00	9,14E+00	-5,21E+01						
GWP – biogenic	kg CO <sub>2</sub> e	-6,87E+01	4,01E-04	3,01E+00	-6,57E+01	0,00E+00	5,89E+00	MND	0,00E+00	0,00E+00	5,71E+01	3,00E+00	-2,68E+01						
GWP – LULUC	kg CO <sub>2</sub> e	7,32E-01	3,35E-03	9,39E-03	7,44E-01	3,82E-03	1,27E-04	MND	0,00E+00	8,14E-05	1,21E-03	3,63E-04	-7,17E-02						
Ozone depletion pot.	kg CFC <sub>11</sub> e	1,13E-05	2,02E-06	1,97E-06	1,53E-05	2,15E-06	1,68E-08	MND	0,00E+00	5,08E-08	1,07E-07	6,78E-07	-3,41E-06						
Acidification potential	mol H <sup>+</sup> e	6,35E-01	4,35E-02	7,37E-02	7,52E-01	6,03E-02	5,16E-04	MND	0,00E+00	9,35E-04	5,74E-03	8,75E-03	-3,79E-01						
EP-freshwater <sup>2)</sup>	kg Pe	5,19E-03	6,03E-05	1,26E-04	5,38E-03	6,25E-05	4,40E-06	MND	0,00E+00	1,81E-06	4,85E-05	9,99E-06	-2,00E-03						
EP-marine	kg Ne	9,91E-02	1,31E-02	1,94E-02	1,32E-01	1,68E-02	1,27E-04	MND	0,00E+00	2,78E-04	9,61E-04	1,38E-03	-4,99E-02						
EP-terrestrial	mol Ne	1,13E+00	1,45E-01	2,50E-01	1,53E+00	1,86E-01	1,38E-03	MND	0,00E+00	3,06E-03	1,10E-02	1,48E-02	-5,71E-01						
POCP (“smog”) <sup>3)</sup>	kg NMVOCe	3,68E-01	4,33E-02	6,35E-02	4,75E-01	5,39E-02	4,15E-04	MND	0,00E+00	9,80E-04	3,17E-03	4,84E-03	-1,73E-01						
ADP-minerals & metals <sup>4)</sup>	kg Sbe	1,06E-03	2,76E-05	1,82E-05	1,10E-03	2,94E-05	6,90E-07	MND	0,00E+00	5,17E-07	3,90E-05	5,24E-06	-2,58E-04						
ADP-fossil resources	MJ	8,85E+02	1,30E+02	6,06E+01	1,08E+03	1,38E+02	1,73E+00	MND	0,00E+00	3,32E+00	1,43E+01	4,06E+01	-6,15E+02						
Water use <sup>5)</sup>	m <sup>3</sup> e depr.	2,79E+02	5,85E-01	2,18E+01	3,02E+02	6,19E-01	2,91E-02	MND	0,00E+00	1,48E-02	3,15E-01	1,85E-01	-8,41E+00						

1) GWP = Global Warming Potential; 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO4e; 3) POCP = Photochemical ozone formation; 4) ADP = Abiotic depletion potential; 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

### ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Particulate matter	Incidence	8,91E-06	8,55E-07	4,58E-07	1,02E-05	8,16E-07	8,53E-09	MND	0,00E+00	2,54E-08	6,74E-08	7,81E-08	-5,19E-06						
Ionizing radiation <sup>6)</sup>	kBq U235e	6,82E+00	6,68E-01	1,29E+00	8,77E+00	7,13E-01	2,38E-02	MND	0,00E+00	1,58E-02	2,26E-01	1,97E-01	-6,20E+00						
Ecotoxicity (freshwater)	CTUe	2,42E+03	1,07E+02	1,94E+02	2,73E+03	1,12E+02	1,84E+00	MND	0,00E+00	2,98E+00	2,69E+01	1,10E+02	-1,30E+03						
Human toxicity, cancer	CTUh	6,82E-07	3,27E-09	1,75E-08	7,02E-07	3,63E-09	1,24E-10	MND	0,00E+00	7,33E-11	3,61E-09	1,79E-08	-6,79E-08						
Human tox. non-cancer	CTUh	2,30E-06	1,08E-07	1,32E-07	2,54E-06	1,13E-07	1,85E-09	MND	0,00E+00	2,95E-09	3,49E-08	3,25E-08	-7,20E-07						
SQP <sup>7)</sup>	-	5,61E+03	9,92E+01	3,88E+02	6,10E+03	1,03E+02	1,07E+00	MND	0,00E+00	3,82E+00	8,86E+00	6,75E+00	-3,67E+02						

6) EN 15804+A2 disclaimer for ionizing radiation, human health. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator; 7) SQP = Land use related impacts/soil quality.

### USE OF NATURAL RESOURCES

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Renew. PER as energy <sup>8)</sup>	MJ	7,85E+02	1,75E+00	1,20E+02	9,07E+02	1,86E+00	1,46E-01	MND	0,00E+00	3,73E-02	1,78E+00	2,95E-01	-1,19E+02						
Renew. PER as material	MJ	5,46E+02	0,00E+00	-2,23E+01	5,23E+02	0,00E+00	-4,91E+01	MND	0,00E+00	0,00E+00	-4,51E+02	-2,37E+01	-3,71E+02						
Total use of renew. PER	MJ	1,33E+03	1,75E+00	9,74E+01	1,43E+03	1,86E+00	-4,90E+01	MND	0,00E+00	3,73E-02	-4,49E+02	-2,34E+01	-4,90E+02						
Non-re. PER as energy	MJ	9,67E+02	1,30E+02	3,03E+02	1,40E+03	1,38E+02	1,72E+00	MND	0,00E+00	3,32E+00	1,42E+01	4,06E+01	-6,15E+02						
Non-re. PER as material	MJ	9,68E+01	0,00E+00	-5,99E+00	9,08E+01	0,00E+00	-1,56E+01	MND	0,00E+00	0,00E+00	-7,14E+01	-3,76E+00	-3,19E+01						
Total use of non-re. PER	MJ	1,06E+03	1,30E+02	2,97E+02	1,49E+03	1,38E+02	-1,39E+01	MND	0,00E+00	3,32E+00	-5,72E+01	3,68E+01	-6,47E+02						
Secondary materials	kg	3,29E+00	4,24E-02	3,23E-01	3,66E+00	4,56E-02	1,67E-03	MND	0,00E+00	9,21E-04	9,89E-03	1,53E-02	-6,74E-01						
Renew. secondary fuels	MJ	7,54E+00	4,35E-04	3,27E+00	1,08E+01	4,54E-04	1,23E-05	MND	0,00E+00	9,29E-06	1,89E-04	3,69E-05	-9,39E-04						
Non-ren. secondary fuels	MJ	4,79E-02	0,00E+00	0,00E+00	4,79E-02	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
Use of net fresh water	m <sup>3</sup>	1,74E+00	1,60E-02	4,39E-01	2,20E+00	1,69E-02	8,45E-04	MND	0,00E+00	4,29E-04	9,08E-03	4,92E-03	-7,72E-01						

8) PER = Primary energy resources.

### END OF LIFE – WASTE

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Hazardous waste	kg	3,44E+01	1,48E-01	5,36E-01	3,51E+01	1,55E-01	7,55E-03	MND	0,00E+00	4,40E-03	3,15E-01	2,59E+00	-6,69E+00						
Non-hazardous waste	kg	1,52E+02	2,52E+00	1,32E+01	1,67E+02	2,62E+00	2,21E-01	MND	0,00E+00	7,22E-02	4,53E+00	2,35E+00	-1,12E+02						
Radioactive waste	kg	3,15E-03	8,92E-04	5,09E-04	4,55E-03	9,52E-04	1,16E-05	MND	0,00E+00	2,22E-05	8,89E-05	0,00E+00	-2,35E-03						

### END OF LIFE – OUTPUT FLOWS

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Components for re-use	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						
Materials for recycling	kg	6,60E-02	0,00E+00	8,30E-03	7,43E-02	0,00E+00	6,04E-01	MND	0,00E+00	0,00E+00	7,32E+00	0,00E+00	0,00E+00						
Materials for energy rec	kg	1,00E-03	0,00E+00	5,24E+00	5,24E+00	0,00E+00	2,69E+00	MND	0,00E+00	0,00E+00	2,81E+01	0,00E+00	-1,05E-01						
Exported energy	MJ	0,00E+00	0,00E+00	6,87E+01	6,87E+01	0,00E+00	0,00E+00	MND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00						

### ENVIRONMENTAL IMPACTS – EN 15804+A1, CML / ISO 21930

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Global Warming Pot.	kg CO <sub>2</sub> e	8,45E+01	8,67E+00	2,08E+01	1,14E+02	9,27E+00	1,49E-01	MND	0,00E+00	2,18E-01	2,84E+00	9,24E+00	-5,09E+01						
Ozone depletion Pot.	kg CFC <sub>11</sub> e	1,07E-05	1,60E-06	1,54E-06	1,39E-05	1,71E-06	1,35E-08	MND	0,00E+00	4,02E-08	8,76E-08	5,39E-07	-2,87E-06						
Acidification	kg SO <sub>2</sub> e	5,24E-01	3,37E-02	5,28E-02	6,11E-01	4,74E-02	4,12E-04	MND	0,00E+00	7,26E-04	4,76E-03	7,37E-03	-3,22E-01						
Eutrophication	kg PO <sub>4</sub> <sup>3</sup> e	1,74E-01	7,05E-03	1,50E-02	1,96E-01	8,43E-03	3,51E-04	MND	0,00E+00	1,65E-04	7,51E-03	7,00E-03	-7,74E-02						
POCP ("smog")	kg C <sub>2</sub> H <sub>4</sub> e	3,59E-02	1,25E-03	4,06E-03	4,12E-02	1,62E-03	2,17E-05	MND	0,00E+00	2,83E-05	2,26E-04	3,15E-04	-1,67E-02						
ADP-elements	kg Sbe	1,02E-03	2,69E-05	2,90E-05	1,08E-03	2,87E-05	6,82E-07	MND	0,00E+00	5,01E-07	3,89E-05	4,91E-06	-2,55E-04						
ADP-fossil	MJ	1,08E+03	1,30E+02	3,19E+02	1,53E+03	1,38E+02	1,72E+00	MND	0,00E+00	3,32E+00	1,42E+01	4,06E+01	-6,16E+02						

### ENVIRONMENTAL IMPACTS – FRENCH NATIONAL COMPLEMENTS

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
ADP-elements	kg Sbe	9,73E-04	2,69E-05	2,89E-05	1,03E-03	2,87E-05	6,82E-07	MND	0,00E+00	5,01E-07	3,89E-05	4,91E-06	-2,55E-04						
Hazardous waste disposed	kg	3,37E+01	1,48E-01	5,78E-01	3,44E+01	1,55E-01	7,55E-03	MND	0,00E+00	4,40E-03	3,15E-01	2,59E+00	-6,69E+00						
Non-haz. waste disposed	kg	1,47E+02	2,52E+00	9,36E+00	1,58E+02	2,62E+00	2,21E-01	MND	0,00E+00	7,22E-02	4,53E+00	2,35E+00	-1,12E+02						
Air pollution	m <sup>3</sup>	3,46E+04	1,25E+03	1,22E+03	3,71E+04	1,35E+03	2,35E+01	MND	0,00E+00	3,96E+01	2,33E+02	1,29E+02	-2,22E+04						
Water pollution	m <sup>3</sup>	5,01E+02	1,11E+01	5,05E+01	5,63E+02	1,18E+01	9,79E-01	MND	0,00E+00	2,34E-01	3,49E+02	3,84E+01	8,69E+01						

### ENVIRONMENTAL IMPACTS – GWP-GHG - THE INTERNATIONAL EPD SYSTEM

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP-GHG <sup>9)</sup>	kg CO <sub>2</sub> e	8,66E+01	8,76E+00	2,13E+01	1,17E+02	9,35E+00	1,48E-01	MND	0,00E+00	2,21E-01	2,88E+00	9,14E+00	-5,21E+01						

<sup>9)</sup> This indicator includes all greenhouse gases excluding biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product as defined by IPCC AR 5 (IPCC 2013). In addition, the characterisation factors for the flows - CH<sub>4</sub> fossil, CH<sub>4</sub> biogenic and Dinitrogen monoxide - were updated in line with the guidance of IES PCR 1.2.5 Annex 1. This indicator is identical to the GWP-total of EN 15804:2012+A2:2019 except that the characterization factor for biogenic CO<sub>2</sub> is set to zero.

## VERIFICATION STATEMENT

### VERIFICATION PROCESS FOR THIS EPD

This EPD has been verified in accordance with ISO 14025 by an independent, third-party verifier by reviewing results, documents and compliancy with reference standard, ISO 14025 and ISO 14040/14044, following the process and checklists of the program operator for:

- This Environmental Product Declaration
- The Life-Cycle Assessment used in this EPD
- The digital background data for this EPD

Why does verification transparency matter? [Read more online](#)

This EPD has been generated by One Click LCA EPD generator, which has been verified and approved by the EPD Hub.

### THIRD-PARTY VERIFICATION STATEMENT

I hereby confirm that, following detailed examination, I have not established any relevant deviations by the studied Environmental Product Declaration (EPD), its LCA and project report, in terms of the data collected and used in the LCA calculations, the way the LCA-based calculations have been carried out, the presentation of environmental data in the EPD, and other additional environmental information, as present with respect to the procedural and methodological requirements in ISO 14025:2010 and reference standard.

I confirm that the company-specific data has been examined as regards plausibility and consistency; the declaration owner is responsible for its factual integrity and legal compliance.

I confirm that I have sufficient knowledge and experience of construction products, this specific product category, the construction industry, relevant standards, and the geographical area of the EPD to carry out this verification.

I confirm my independence in my role as verifier; I have not been involved in the execution of the LCA or in the development of the declaration and have no conflicts of interest regarding this verification.

Imane Uald lamkaddam, as an authorized verifier acting for EPD Hub Limited  
11.07.2024

